



(19)

(11) Publication number: 0

Generated Document.

# PATENT ABSTRACTS OF JAPAN

(21) Application number: 01154279

(51) Intl. Cl.: A61M 1/18

(22) Application date: 16.06.89

(30) Priority:

(43) Date of application  
publication: 25.01.91

(84) Designated contracting  
states:

(71) Applicant: TERUMO CORP

(72) Inventor: MURAMOTO TOMONO  
SAKAI SATORU

(74) Representative:

## (54) METHOD AND DEVICE FOR DETECTING LEAK OF HOLLOW FIBER MEMBRANE TYPE LIQUID PROCESSOR

(57) Abstract:

**PURPOSE:** To detect the presence and absence of leak even when a hollow fiber membrane with a full extended tip exists in a hollow fiber bundle by detecting a moving distance in a route means on a boundry between charged water and gas with pressure drop by using a gauge or a sensor.

**CONSTITUTION:** A gas lead-in port opening/closing valve 9a is closed and a charging water lead-in port opening/closing valve 8a is opened. Then, charging water (RO water) is charged through a route tube body 7 and a blood port 5b into a hollow fiber membrane 2a. Continuously, the opening/closing valve 8a is closed and the gas lead-in port opening/closing valve 9a is opened.

Then, pressurization with high pressure is executed by a pressurizing pump. After the pressurization, the opening/closing valve 9a is closed and left for prescribed time. When there is a pin hole, etc., in any hollow fiber membrane 2a, the RO water is leaked from the part and the internal pressure falls down by the leakage. Then, in a leak discriminating part A, a boundary 11 between the RO water and air is moved to the side of the hollow fiber membrane 2a. Accordingly, by detecting the moving quantity of this boundary 11 with a gauge 12 and calculating the moving quantity for each unit time, the presence and absence of the leak can be discriminated.

COPYRIGHT: (C)1991,JPO&Japio

